



Large Genie

Benchtop High Output Water Systems



**Daily pure water production
up to 1,900 L from tap water!**

Overview

The Large Genie series is a mini high output water purification system introduced by RephiLe. Despite its small size, Large Genie is capable of producing large volumes of purified water with reliable quality. It is an ideal solution for users who need large quantity high quality pure water per day but have limited lab space. With a Large Genie, you can use your lab room more efficiently and enjoy numerous ancillary advantages associated with its small footprint. Most importantly, the system potentially can have a positive impact on your overall operational costs and helps improving the profitability position of your facility.

There are five different configurations- G, U, E, C and R in this series. No matter you need ultrapure water, EDI pure water, RO water or clinical grade of purified water, you can always find one model for your needs.

The systems are manufactured in ISO 9001:2015 and ISO 14001:2015 certified manufacturing sites. The systems are CE and RoHS certified.

A small footprint
to maximize
your lab space



Selection Guide

Large Genie has 5 different configurations: G, U, E, C and R
Genie G & U produce two types of water from one system with TOC monitoring.

Pure water production rate:
EDI pure water: 30/60 liters per hour
RO pure water: 40/80 liters per hour
Clinical laboratory reagent water: up to 2 liters per min

System type	Genie G 30 / 60	Genie U 40 / 80	Genie E 30 / 60	Genie C 40 / 80	Genie R 40 / 80
Production					
Ultrapure water	●	●			
EDI pure water	●		●		
Clinical laboratory reagent water				●	
RO pure water		●			●

Features




Easy-to-place

- Built-in pretreatment pack including prefiltration, chlorine removal and anti-scaling media; Generally no extra pretreatment needed
- Placement flexibility-wall-mounted, on the bench or on top of a distribution module (optional)
- Modular design. Plug and play connections for quick install



Easy-to-track

- RFID tracking of consumables, RO membranes and accessories to ensure optimal system performance and provide users with real-time operational intelligence
- Enhanced data management stores up to two years of historical information for service and review
- The ability to export and print data and log-in requirements are built into the system



Easy-to-use

- “1+N mode” - one water system can drive N units of dispenser (Up to 10 now and can be upgraded further more).
- A RephiBio filter can be embraced to produce pyrogen, nuclease and bacteria free water for critical applications.



Easy-to-control

- Large Genie equips with multiple touch screens which are highly responsive, latex glove friendly, and perfect for wet labs.
- Intuitive display with comprehensive data views. No need to use additional paperwork or operating checklists.
- 9 display languages for selection
- RephiLink Mobile App enables remote control of the systems



Easy-to-maintain

- No tools are needed for system maintenance and simple service.
- Automatic system shut-off upon detection of any water leakage



Compact size



Light weight



Low noise



Low shipping cost



Environmentally friendly

Main Components

Control Console: Command and control center



- 8-inch touch screen with highly intuitive navigation program, allowing total control and easy operation of the system
- Comfortable viewing and operation with built in viewing angle and flexible placement by users
- Operable with gloves and wet hands
- Robust screen: easy to clean, resistant to scratches

Remote Dispenser: Smart and flexible

- Manual and volumetric dispensing, adjustable dispensing rate, and water quality monitoring
- Ergonomic dispenser allowing one-handed operation and control
- Operable with gloves and wet hands
- Height adjustable and 360 degree rotatable on an anti-skid base



Cartridges: Powerful key of purification

- Improved stability of water quality & efficiency of polishing resins due to optimized flow design
- High pressure rated housings, proprietary sealing, and double O-ring design ensuring operational confidence
- A worry-free installation with two verifications: labels and RFID recognition

Reservoir

- 30-350 liters separate tank available for selection. Smooth inner surface to minimize biofilm formation and algal growth
- Provision for easy cleaning and fully drainable; Spray ball installation for efficient, effective and dependable cleaning
- Unique reinforcing-bar design to prevent deformation



Quality: Hassle free for you

RO
(for G, U, E, C & R)

- Stable RO permeability over a wide range of water temperatures
- Optimized RO-reject water recovery loop to maximize water efficiency

EDI
(for G & E)

- Exceptionally stable in producing high quality Type II water
- Consistently and predictably remove ionic species, including weakly ionized species
- A chemical-free process, free of safety, regulatory and environmental concerns

U PACK
(for G & U)

- Two ultrapure cartridge options: general type and ultralow TOC type
- On-line TOC measurement based on complete oxidation methodology

TANK


- Consistent and accurate tank water level monitoring with a built-in continuous liquid level sensor
- Optional tank recirculation model guarantees water quality in the tank (Not for G or C models)
- Mercury-free germicidal UVC LED lamp (peak emission wavelength at 265 nm) equipped in tank sanitization module

Advantages


RO packs
Specially made RO pack with increased flow rates and reduced size





Silent pumps
Compact with low noise

Mercury Free 


LED UVC Lamp
Mercury-free germicidal lamp with peak emission wavelength at 265 nm



Inline LED UVC lamp 

Tank LED UVC lamp 

Optimization of EDI product water stored in the reservoir
Diversion to drain if EDI pure water fails to pass a set point of resistivity. Optional control. Free to select on/off function. (Genie G/E)



Modular Design to improve productivity and maintain the flexibility



Wall-mounted
Wall mount bracket 

On the bench 

Stacked 


Prefiltration & distribution module
It contains: activated carbon, PP particle filter, softener, a pump, a UV lamp, a filter and a resistivity sensor

Distribution module
It contains: a pump, a UV lamp, a filter and a resistivity sensor





Flow Diagrams


Large Genie G




Large Genie U




Large Genie E



Large Genie C



Large Genie R



Specifications

	Genie G	Genie U	Genie E	Genie C	Genie R
Feed water					
Conductivity	< 2000 $\mu\text{S}/\text{cm}$ @ 25 °C (TDS < 1000 ppm)				
Temperature	5 - 35 °C (41 - 95 °F)				
Pressure	0.2 - 0.6 MPa (2.0 - 6.0 bar)				
TOC	< 2000 ppb				
Product water	Type I + Type II	Type I + RO	Type II	CLRW	RO
Flow rate	30 / 60 L/hr	40 / 80 L/hr	30 / 60 L/hr	40 / 80 L/hr*	40 / 80 L/hr
HP Dispenser rate	0-2 L/min	0-2 L/min	0-2 L/min	0-2 L/min	0-2 L/min
UP Dispenser rate	0-2 L/min	0-2 L/min	-	-	-
Main system specifications					
Width x Depth x Height	570 mm x 460 mm x 705 mm (22.5 in x 18.2 in x 27.5 in)				
Weight (Net)	46 kg	38 kg	44 kg	38 kg	36 kg
Input voltage	220 VAC	100-240 VAC	220 VAC	100-240 VAC	100-240 VAC
Frequency	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz
Power	< 600 W	< 250 W	< 600 W	< 250 W	< 250 W

*RO production rate

Product Water Quality

	Ultrapure water (Type I)	EDI water (Type II)	CLRW	RO water
RO rejection		97 to 98% ionic content rejection (new RO cartridge)	> 99% organics rejection	> 99% particulates & bacteria rejection
Resistivity (@25°C)	18.2 M Ω ·cm	> 5 M Ω ·cm (Typically 10-16 M Ω ·cm)	> 10 M Ω ·cm (Typically > 16 M Ω ·cm)*	> 0.05 M Ω ·cm (< 20 $\mu\text{S}/\text{cm}$)*
TOC	< 2 ppb**	< 30 ppb***	< 30 ppb***	N/A
Microorganisms****	< 0.001 cfu/ml	< 10 cfu/ml	< 1 cfu/ml	N/A
Particles (> 0.2 μm)****	No particles with size > 0.22 μm	N/A	No particles with size > 0.22 μm	N/A
Pyrogens (endotoxins)*****	< 0.001 Eu/ml	N/A	N/A	N/A
RNase*****	< 0.5 pg/ml	N/A	N/A	N/A
DNase*****	< 10 pg/ml	N/A	N/A	N/A
Silica	N/A	N/A	< 1 cfu/ml	N/A


*When feed water conductivity is < 500 $\mu\text{S}/\text{cm}$

**In the appropriate operating conditions, otherwise typically \leq 5 ppb.

***In the appropriate operating conditions

**** with a 0.2 μm final filter or a RephiBio filter

***** with a RephiBio filter



Main Applications



Ultrapure water

- HPLC mobile phase preparation
- Preparation of reagent blank solutions
- As sample diluent for GC, HPLC, ICP-MS, AA and other analytical techniques
- Preparation of buffers and culture media for mammalian cell culture
- Preparation of molecular biology reagents



EDI water

- Preparation of chemical and bio-reagents
- Preparation of culture media
- Preparation of solutions for chemical analysis such as HPLC and ICP
- For clinical analyzers
- Medical device and equipment rinsing
- For serum and blood fractionation
- For ophthalmics



Clinical laboratory reagent water

- Dilution of clinical reagents, samples and detergents
- Automatic medical device and equipment rinsing
- Reaction cuvettes cleaning
- Feeding washing stations for probe tips and stirrer paddles
- Temperature controlled Incubator baths
- An interface between syringe and sample



RO water

- Glassware cleaning
- Water bath water
- Autoclave
- Feed water for laboratory animals

Ordering Info

Description	Cat. No.
Genie G 30 Water System set with TOC	RG0G030T0K
Genie G 60 Water System set with TOC	RG0G060T0K
Genie U 40 Water System set with TOC	RG0U040T0K
Genie U 80 Water System set with TOC	RG0U080T0K
Genie E 30 Water System set	RG0E03000K
Genie E 60 Water System set	RG0E06000K
Genie C 40 Water System set	RG0C04000K
Genie C 80 Water System set	RG0C08000K
Genie R 40 Water System set	RG0R04000K
Genie R 80 Water System set	RG0R08000K

Water Quality Compliance

Quality of ultrapure water meets or exceeds ASTM, CLSI, CAP, and ISO Type I water.

EDI product water meets or exceeds Type II water quality as defined by ASTM, CAP, CLSI and ISO 3696 / BS 3997 and also complies with the Purified Water requirements from the European and U.S. Pharmacopoeia.

Quality of CLRW meets clinical laboratory reagent water (CLRW) standards that complies with the CLSI® guideline.

RephiLe Bioscience, Ltd.

Toll Free: +1-855-RephiLe (+1-855-737-4453)
E-mail: info@rephile.com

All rights reserved © 2024 RephiLe Bioscience, Ltd.
RephiLe and Genie are registered trademarks of RephiLe Bioscience, Ltd.
All other trademarks mentioned are the property of their respective owners.
TM and ® may be omitted in this brochure.

Literature: RFPRI692403